



Notes

- 1) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 2) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 4) The area above the fan discharge must be unobstructed.
- 5) Piping must not be supported by the tower inlet or outlet connections.
- 6) Unit weights include selected accessories.
- 7) M = Motor location.

Right Hand Unit

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-1214A-1x1	7000	13210	5080	13'-10 1/2"	7'-11 1/4"	8'-4"	4'-10 3/8"
PT2-1214A-2x1	7650	13860	5730	14'-10 1/2"	8'-11 1/4"	9'-4"	4'-10 3/8"
PT2-1214A-3x1	8140	14360	6220	15'-10 1/2"	9'-11 1/4"	10'-4"	4'-10 3/8"
PT2-1214A-4x1	8380	14890	6220	17'-4 1/2"	11'-5 1/4"	10'-4"	6'-4 3/8"
PT2-1214A-5x1	8870	15380	6710	18'-4 1/2"	12'-5 1/4"	11'-4"	6'-4 3/8"

ORDER NO:

DATE:



**BALTIMORE
AIRCOIL COMPANY**

**PT2 Single Cell Unit Print
Internal Belt Drive**

DRAWING NUMBER:
GEN-PT2-1214A