



Model Number	Approx, Shipping Weight	Approx, Operating Weight	Heaviest Section Weight	F	Н
PCC-0177-0718N010	12260	19130	9550	4'-0 5/8"	14'-3 7/8"
PCC-0214-0718N020	12460	19330	9740	4'-0 5/8"	14'-3 7/8"
PCC-0222-0718N015	13670	20630	10960	4'-0 5/8"	14'-3 7/8"
PCC-0267-0718N030	14020	20970	11300	4'-0 5/8"	14'-3 7/8"
PCC-0232-0718N015	14140	21130	11430	4'-0 5/8"	14'-3 7/8"
PCC-0278-0718N030	14960	21980	12240	4'-8 1/8"	14'-11 3/8"
PCC-0300-0718N040	15300	22320	12580	4'-8 1/8"	14'-11 3/8"
PCC-0324-0718N020	16190	23280	13470	4'-8 1/8"	14'-11 3/8"
PCC-0349-0718N020	20370	27700	17640	5'-11 1/8"	16'-2 3/8"



- 1) Drawings are not to scale. All dimensions are in feet
- Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) Dimensions showing location of coil and basin connections are approximate and should not be used for prefabrication of connecting piping.
- 4) For weight loadings and support requirements, refer to the suggested steel support drawing.
- Heaviest section is the combined weight of fan and coil sections, refer to the P-Series Counterflow Induced Draft Coil Products rigging and assembly manual for suggested lifting method.
- 6) The area above the discharge must be unobstructed.
- 7) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
- 8) M = Motor location



Right Hand Unit

ORDER NO:



PCC Evaporative Condenser Tabulated Unit Print

DRAWING NUMBER:

**UP-PCC-0718**