





Notes

- 1) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 2) Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) Field piping should be fabricated at time of installation. Pre-fabrication of pipe work is not recommended.
- 4) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
- 5) For weight loadings and support requirements, refer to the suggested unit support drawing.
- 6) The area above the fan discharge must be unobstructed.
- 7) Due to height limitations on truck shipments, some items shown may ship loose for field installation.
- 8) Weights and dimensions are for base structure units with no accessories or optional features, values may vary depending upon unit configuration.
- 9) Connection sizes and locations are selected for pump suction applications at the designed flow rates. Sizes and locations may vary depending upon configuration options and design conditions.
- 10) Inlet is Studded Bolt Circle for mating to a 150# class ASME Flange.



Model Number	Operating Weight	Shipping Weight	Heaviest Section Weight
XES15E-1212-10EN	17260	8200	4430
XES15E-1212-10FN	17300	8240	4470
XES15E-1212-10GC	17360	8300	4530
XES15E-1212-10GN	17360	8300	4530
XES15E-1212-10HC	17380	8320	4550
XES15E-1212-10HN	17380	8320	4550
XES15E-1212-10JN	17480	8420	4650
S15E-1212-10KN	17510	8450	4680
S15E-1212-10LC	17760	8700	4930
S15E-1212-10LN	17760	8700	4930
S15E-1212-10MN	17880	8820	5050



ORDER NO:

DATE: **3/18/2014**



BALTIMORE AIRCOIL COMPANY

**Series 1500 Single Cell Unit Print
1212-10**

DRAWING NUMBER:
UP-XE-S15E-1212-10