



- Notes
- 1) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
  - 2) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
  - 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
  - 4) The area above the fan discharge must be unobstructed.
  - 5) Piping must not be supported by the tower inlet or outlet connections.
  - 6) Unit weights include selected accessories.
  - 7) M = Motor location.
  - 8) External motor assembly ships loose for field installation.

Right Hand Unit

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-0709A-1x1	3445	6205	2505	11'-4 7/8"	6'-9 1/4"	7'-0 3/4"	3'-8 7/8"
PT2-0709A-2x1	3860	6620	2920	12'-4 7/8"	7'-9 1/4"	8'-0 3/4"	3'-8 7/8"
PT2-0709A-3x1	4150	6910	3220	13'-4 7/8"	8'-9 1/4"	9'-0 3/4"	3'-8 7/8"
PT2-0709A-4x1	4390	7330	3220	14'-4 7/8"	9'-9 1/4"	9'-0 3/4"	4'-8 7/8"
PT2-0709A-5x1	4610	7550	3440	15'-4 7/8"	10'-9 1/4"	10'-0 3/4"	4'-8 7/8"

ORDER NO:

DATE:



**BALTIMORE AIRCOIL COMPANY**

**PT2 Single Cell Unit Print  
External Belt Drive**

DRAWING NUMBER:  
**GEN-PT2-0709A**