



Notes

- 1) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 2) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 4) The area above the fan discharge must be unobstructed.
- 5) Piping must not be supported by the tower inlet or outlet connections.
- 6) Unit weights include selected accessories.
- 7) M = Motor location.
- 8) External motor assembly ships loose for field installation.

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-0809A-1x3	11890	21120	2860	13'-6 3/8"	8'-10 3/4"	7'-2 1/4"	5'-8 7/8"
PT2-0809A-2x3	12790	22020	3160	14'-6 3/8"	9'-10 3/4"	8'-2 1/4"	5'-8 7/8"
PT2-0809A-3x3	14250	23480	3510	15'-6 3/8"	10'-10 3/4"	9'-2 1/4"	5'-8 7/8"
PT2-0809A-4x3	15090	25290	3510	17'-7 7/8"	13'-0 1/4"	9'-2 1/4"	7'-10 3/8"
PT2-0809A-5x3	15750	25950	3730	18'-7 7/8"	14'-0 1/4"	10'-2 1/4"	7'-10 3/8"

ORDER NO:

DATE:



BALTIMORE AIRCOIL COMPANY

**PT2 Three Cell Unit Print
External Belt Drive**

DRAWING NUMBER:
GEN-PT2-0809A 3-CELL