



FACE A
(CONNECTIONS TYPICAL EACH END)



FACE D



FACE C

Notes

- 1) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 2) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 4) The area above the fan discharge must be unobstructed.
- 5) Piping must not be supported by the tower inlet or outlet connections.
- 6) Unit weights include selected accessories.
- 7) M = Motor location.
- 8) External motor assembly ships loose for field installation.

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-0812A-1x3	14070	26470	3220	13'-8"	9'-3 1/4"	6'-11 3/4"	6'-1 3/8"
PT2-0812A-2x3	15120	27520	3540	14'-8"	10'-3 1/4"	7'-11 3/4"	6'-1 3/8"
PT2-0812A-3x3	16620	29020	3880	15'-8"	11'-3 1/4"	8'-11 3/4"	6'-1 3/8"
PT2-0812A-4x3	17340	30940	3880	17'-11"	13'-6 1/4"	8'-11 3/4"	8'-4 3/8"
PT2-0812A-5x3	18300	31890	4200	18'-11"	14'-6 1/4"	9'-11 3/4"	8'-4 3/8"

ORDER NO:

DATE:



BALTIMORE AIRCOIL COMPANY

PT2 Three Cell Unit Print
External Belt Drive

DRAWING NUMBER:
GEN-PT2-0812A 3-CELL