



Notes

- 1) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 2) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 4) The area above the fan discharge must be unobstructed.
- 5) Piping must not be supported by the tower inlet or outlet connections.
- 6) Unit weights include selected accessories.
- 7) M = Motor location.
- 8) Heaviest section is a cell's mechanical section mounted to fill casing section.

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-1218A-1xT	21500	40270	6920	16'-6 3/8"	9'-9 5/8"	8'-7 7/8"	6'-9 5/8"
PT2-1218A-2xT	22900	41670	7615	17'-6 3/8"	10'-9 5/8"	9'-7 7/8"	6'-9 5/8"
PT2-1218A-3xT	25850	44620	9090	18'-6 3/8"	11'-9 5/8"	10'-7 7/8"	6'-9 5/8"
PT2-1218A-4xT	24620	43918	8180	20'-4 3/8"	12'-11 5/8"	10'-7 7/8"	7'-11 5/8"
PT2-1218A-5xT	27762	47060	9751	21'-4 1/2"	13'-11 5/8"	11'-7 7/8"	7'-11 5/8"

ORDER NO:

DATE:



**BALTIMORE
AIRCOIL COMPANY**

**Unit Print
PT2 Two Cell 24'x18'**

DRAWING NUMBER: