



MODEL NO.	APPROX. SHIPPING WEIGHT	APPROX. OPERATING WEIGHT
VCA-605A	27750	43190
VCA-684A	27770	43210
VCA-754A	27810	43250
VCA-808A	27820	43260
VCA-762A	31790	47440
VCA-840A	31830	47480
VCA-902A	37840	47490
VCA-879A	35850	51720
VCA-942A	35860	51730
VCA-1026A	35940	51810
VCA-982A	38340	54350
VCA-1082A	38420	54430
VCA-1160A	38730	54740
VCA-1075A	42590	58840
VCA-1170A	42670	58920
VCA-1252A	42840	59090
VCA-1321A	42980	59230
VCA-S870A	31100	46750
VCA-S932A	31110	46760
VCA-S972A	35080	50940
VCA-S1071A	35160	51020
VCA-S1019A	37630	53640
VCA-S1124A	37700	53710
VCA-S1204A	37710	53720

Notes

- 1) All dimensions are in feet and inches. Weights are in pounds and do not include options and accessories.
- 2) Supporting steelwork and anchor bolts to be designed and furnished by others.
- 3) All supporting steel must be flush and level at top.
- 4) Each beam should be designed, as a minimum, for 65% of the total unit operating weight applied as a uniformly distributed load.
- 5) Beams should be selected in accordance with accepted structural practice, maximum deflection of beam under the unit to be 1/360 of span, not to exceed 1/2 inch.
- 6) If vibration isolation rails are used between unit and supporting steel, be certain to allow for the length of the vibration rails when determining length of supporting steel. Vibration rail length and mounting hole locations may differ from those of the unit. Refer to vibration isolator manufacturer drawings for this data.
- 7) Do not use this drawing to size point vibration isolators.

ORDER NO: _____

DATE: _____



Baltimore Aircoil

VCA Unit Support
12'x24'

DRAWING NUMBER: _____