



Notes

- 1) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 2) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 4) The area above the fan discharge must be unobstructed.
- 5) Piping must not be supported by the tower inlet or outlet connections.
- 6) Unit weights include selected accessories.
- 7) M = Motor location.

Right Hand Unit

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-1009A-1x1	4310	7750	3320	13'-0 1/4"	7'-2 1/4"	8'-4"	4'-1 3/8"
PT2-1009A-2x1	4680	8120	3670	14'-0 1/4"	8'-2 1/4"	9'-4"	4'-1 3/8"
PT2-1009A-3x1	5020	8460	3990	15'-0 1/4"	9'-2 1/4"	10'-4"	4'-1 3/8"
PT2-1009A-4x1	5260	9240	3990	16'-0 1/4"	10'-2 1/4"	10'-4"	5'-1 3/8"
PT2-1009A-5x1	5540	9520	4270	17'-0 1/4"	11'-2 1/4"	11'-4"	5'-1 3/8"

ORDER NO:

DATE:



**BALTIMORE
AIRCOIL COMPANY**

**PT2 Single Cell Unit Print
Internal Belt Drive**

DRAWING NUMBER:
GEN-PT2-1009A