

Model Number	Approx, Shipping Weight	Approx, Operating Weight
PCC-2159-2440N160	96120	143700
PCC-1710-2440N060	99728	147590
PCC-1948-2440N080	109968	158450
PCC-2143-2440N120	110288	158770
PCC-2306-2440N160	111168	159650
PCC-2436-2440N200	111268	159750
PCC-2060-2440N080	126240	175960
PCC-2210-2440N100	134240	184460
PCC-2250-2440N120	126560	176280
PCC-2302-2440N120	134440	184660
PCC-2345-2440N160	120880	170180
PCC-2468-2440N160	135320	185540
PCC-2540-2440N200	127540	177260
PCC-2615-2440N200	135420	185640
PCC-2734-2440N240	136424	186650

PLAN VIEW

Notes

- 1) Drawings are not to scale. All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 2) Operating weight and weight loading are for units with water level in basin at overflow.
- 3) Unit support beams and anchor bolts to be designed and furnished by others.
- 4) Support beams must be flush and level at top.
- 5) All supporting steelwork must be designed in accordance with accepted structural practice. Maximum deflection of steelwork under unit to be 1/360 of span, not to exceed 1/2".
- 6) Each beam should be designed, as a minimum, for 65% of the total unit operation weight applied as a uniformly distributed load.

ORDER NO:

DATE:



PCC Evaporative Condenser
Tabulated Steel Support - Plan A

DRAWING NUMBER: SS-PCC-2440