



Notes

- 1) Drawings are not to scale. All dimensions are in feet and inches.
- 2) Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) Dimensions showing location of coil and basin connections are approximate and should not be used for prefabrication of connecting piping.
- 4) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 5) Heaviest section is the combined weight of fan and coil sections, refer to the P-Series Counterflow Induced Draft Coil Products rigging and assembly manual for suggested lifting method.
- 6) The area above the discharge must be unobstructed.
- 7) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
- 8) M = Motor location

Model Number	Approx. Shipping Weight	Approx. Operating Weight	Heaviest Section Weight	F	H
PCC-0544-1220N040	23837	35730	19273	4'-0 5/8"	17'-11 7/16"
PCC-0431-1220N015	24739	36700	20173	4'-8 1/8"	18'-6 15/16"
PCC-0491-1220N020	27299	39420	22733	4'-8 1/8"	18'-6 15/16"
PCC-0540-1220N030	27379	39500	22813	4'-8 1/8"	18'-6 15/16"
PCC-0581-1220N040	27599	39720	23033	4'-8 1/8"	18'-6 15/16"
PCC-0614-1220N050	27624	39740	23058	4'-8 1/8"	18'-6 15/16"
PCC-0519-1220N020	31367	43800	26803	4'-0 5/8"	17'-11 7/16"
PCC-0557-1220N025	33367	45920	28803	4'-0 5/8"	17'-11 7/16"
PCC-0567-1220N030	31447	43880	26883	4'-0 5/8"	17'-11 7/16"
PCC-0580-1220N030	33417	45970	28853	4'-0 5/8"	17'-11 7/16"
PCC-0591-1220N040	30027	42350	25463	4'-0 5/8"	17'-11 7/16"
PCC-0622-1220N040	33637	46190	29073	4'-0 5/8"	17'-11 7/16"
PCC-0640-1220N050	31692	44120	27128	4'-0 5/8"	17'-11 7/16"
PCC-0659-1220N050	33662	46220	29098	4'-0 5/8"	17'-11 7/16"
PCC-0689-1220N060	33913	46470	29349	4'-0 5/8"	17'-11 7/16"

ORDER NO:

DATE:



BALTIMORE AIRCOIL COMPANY

PCC-Evaporative Condenser
Tabulated Unit Print

DRAWING NUMBER:
UP-PCC-1220