


1) Drawings are not to scale. Refer to submittal drawings for actual dimensions and weights. All dimensions are in feet and inches, Weights are in pounds.

 Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.

 Dimensions showing location of coil and basin connections are approximate and should not be used for prefabrication of connecting piping.
For weight loadings and support requirements, refer to the suggested steel support drawing.
Heaviest section is the combined weight of fan and coil sections, refer to the rigging and assembly manual for suggested lifting method.
The area above the discharge must be unobstructed.

7) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
8) M = Motor location.



FACE C

PFI Closed Circuit Cooling Tower Tabulated Unit Print DRAWING NUMBER: UP-PFI-1224

Approx, Approx, Heaviest Shipping Section Operating Weight Weight Weight Model Number н F 4'-0 5/8" 17'-0 3/4" PFI-1224N-2DXDS-X2 40590 10930 27070 PFI-1224N-2DXES-X2 28880 42490 11830 4'-8 1/8" 17'-8 1/4" 4'-0 5/8" 17'-0 3/4" PFI-1224N-3DXDS-X2 31420 46730 13100 PFI-1224N-3DXES-X2 33790 49190 14280 5'-3 5/8" 18'-3 3/4" 4'-8 1/8" 17'-8 1/4" PFI-1224N-4DXDS-X2 34980 14880 51400 PFI-1224N-4DXES-X2 37950 55150 16360 5'-11 1/8" 18'-11 1/4" 5'-3 5/8" 18'-3 3/4" PFI-1224N-5DXDS-X2 40890 59780 17830 19'-5 3/4" PFI-1224N-5DXES-X2 42900 61880 18830 6'-5 5/8" 5'-11 1/8" 18'-11 1/4" PFI-1224N-6DXDS-X2 38870 56840 16820 PFI-1224N-6DXES-X2 7'-1 1/8" 20'-1 1/4" 40940 58980 17850

ORDER NO:



BALTIMORE AIRCOIL COMPANY

DATE: